

# Maxx® (Model 89076-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

			0
	Bearings & Bushings		Cush Drive Components
5106A	Ball bearing, black rubber sealed (15x24x5mm) (2)	6465	Cush drive key/ pin/ elastomer damper
5107A	Ball bearing, black rubber sealed (17x26x5mm) (2)	7793X	Housing, cush drive (front & rear halves)
5196A	Ball bearing, black rubber sealed (20x32x7mm) (2)	6447	Spur gear, 46-tooth (1.0 metric pitch)
5099A	Ball bearing, black rubber sealed (6x16x5mm) (2)	6447X	Spur gear, 46-tooth, steel (1.0 metric pitch)
2728	Ball bearings (5x8x2.5mm) (2)	6448	Spur gear, 50-tooth (1.0 metric pitch)
5119A 5120A	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, black rubber sealed (12x18x4mm) (2)	6448X 6449	Spur gear, 50-tooth, steel (1.0 metric pitch) Spur gear, 54-tooth (1.0 metric pitch)
5120A 5180A	Ball bearings, black rubber sealed (12/10/4/11/11) (2)	6449X	Spur gear, 54-tooth (1.0 metric pitch)
51007	Ball bearings, blue rubber sealed (12x21x5mm) (2)	04457	
7020	Ball bearings, blue rubber sealed (8x12x3.5mm) (2)		Differential Components
	Body & Accessories	8981	Carrier, differential/ x-ring gasket/ o-ring (2)/ 10x19.5x0.5 TW
9015	Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder	8980 5136X	Differential kit, center (complete)
8915	screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9)	8949	Differential oil kit (1 each: 10K, 30K, 50K weights)  Differential output yoke assembly, front or rear (assembled with
8910	Body reinforcement set, Maxx® (fits #8911 body)	0343	external-splined half shaft)
8913	Body support, rear/ 3x10mm CS (4) (fits #8911 body)	8982	Gear set, differential (output gears (2)/ spider gears (4)/ spider gear
8911	Body, Maxx® (clear, untrimmed, requires painting)/ window		shaft (2)/ output shaft (2)/ 2.5X13.8 pin (2))
	masks/ decal sheet	8988	Gear, center differential, 44-tooth
8911A	Body, Maxx®, blue (painted)/ decal sheet	5041	Grease, premium high performance (20cc)
8914	Body, Maxx®, heavy duty (clear, untrimmed, requires painting)/	8985	Input gear, transmission, 22-tooth/ 2.5x12mm pin
8911T	window masks/ decal sheet Body, Maxx®, orange (painted)/ decal sheet	8986 <b>5130</b>	Input shaft, transmission
8911X	Body, Maxx®, ProGraphix® (graphics are printed, requires paint	5135	Oil, differential (100K weight) (.7 oz (20cc)) Oil, differential (10K weight)
001170	& final color application)/ decal sheet	5040	Oil, differential (20M weight) (standard)
8911R	Body, Maxx®, red (painted)/ decal sheet	5136	Oil, differential (30K weight)
8917	Skid plate, roof (body) (black)/ 3x10mm CS (4)	5137	Oil, differential (50K weight)
8917X	Skid plate, roof (body) (blue)/ 3x12mm CS (4)	8989	Output gear, center differential, hardened steel (2)
8917G	Skid plate, roof (body) (green)/ 3x12mm CS (4)	8978	Ring gear, differential/ pinion gear, differential (front)
8917T	Skid plate, roof (body) (orange)/ 3x12mm CS (4)	8977	Ring gear, differential/ pinion gear, differential (rear)
8917R 8917A	Skid plate, roof (body) (red)/ 3x12mm CS (4)	8953	Stub axle assembly, outer (front or rear) (assembled with internal-
8912X	Skid plate, roof (body) (white)/ 3x12mm CS (4) Tailgate protector, blue/ 3x15mm flat-head screw (4)		splined half shaft)
8912G	Tailgate protector, green/ 3x15mm flat-head screw (4)		Driveline Components
8912T	Tailgate protector, orange/ 3x15mm flat-head screw (4)	8952X	Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (2)
8912R	Tailgate protector, red/ 3x15mm flat-head screw (4)	8952G	Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear) (2)
8912A	Tailgate protector, white/ 3x15mm flat-head screw (4)	8952	Carriers, stub axle (left & right)
8912	Tailgate protector/ 3x15mm flat-head screw (4)	8952A	Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rear) (2)
	Bumpers & Skidplates	8952R	Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2)
8933	<u> </u>		
	bumper mount, front	8951	Drive cup (1)/ 4x15.8mm screw pin (use only with #8950X, 8950A
8934	Bumper mount, front Bumper mount, rear	8951	Drive cup (1)/ 4x15.8mm screw pin (use only with #8950X, 8950A driveshaft)
8934 8935	·	8954	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1)
8934 8935 <b>8935X</b>	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit)		driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully
8934 8935 <b>8935X</b> 8936	Bumper mount, rear Bumper, front <b>Bumper, front (for use with #8990 LED light kit)</b> Bumper, rear	8954 8950	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1)
8934 8935 <b>8935X</b> 8936 <b>8936X</b>	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit)	8954 8950 8955	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum
8934 8935 <b>8935X</b> 8936 <b>8936X</b> 8945	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center	8954 8950	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1)
8934 8935 <b>8935X</b> 8936 <b>8936X</b>	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, front (1), rear (1)	8954 8950 8955	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for
8934 8935 <b>8935X</b> 8936 <b>8936X</b> 8945 8944	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, front (1), rear (1)	8954 8950 8955 <b>8950A</b>	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for
8934 8935 <b>8935X</b> 8936 <b>8936X</b> 8945	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, front (1), rear (1)  HIRSSIS & ATTACHIERUS Battery hold-down/ mounts (front & rear)/ battery compartment	8954 8950 8955 <b>8950A</b> <b>8950X</b>	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set)
8934 8935 <b>8935X</b> 8936 <b>8936X</b> 8945 8944	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, front (1), rear (1)  Chassis & Attachinghis Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads	8954 8950 8955 <b>8950A</b>	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized,
8934 8935 <b>8935X</b> 8936 <b>8936X</b> 8945 8944	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, front (1), rear (1)  HIRSES & ATTRICTURE Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder	8954 8950 8955 <b>8950A</b> <b>8950X</b>	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)
8934 8935 <b>8935X</b> 8936 <b>8936X</b> 8945 8944	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, front (1), rear (1)  Chassis & Attachinghis Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads	8954 8950 8955 <b>8950A</b> <b>8950X</b>	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized,
8934 8935 8935X 8936 8936X 8945 8944 8919	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, front (1), rear (1)  Chassis & Attronion  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3)	8954 8950 8955 <b>8950A</b> <b>8950X</b>	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, blue-anodized,
8934 8935 8935X 8936 8936X 8945 8944 8919 8915 8924	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, front (1), rear (1)  Chassis & Attronionion Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front	8954 8950 8955 <b>8950A</b> <b>8950X</b> 8447A 8447X	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)
8934 8935 8935X 8936 8936X 8945 8944 8919 8915 8924 8933 8934	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  Chassis & Attachiller  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear	8954 8950 8955 8950A 8950X 8447A 8447X	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)
8934 8935 8935X 8936 8936X 8945 8944 8919 8915 8924 8933 8934 8935	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  GIRSSIS & ATRICTION Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front	8954 8950 8955 8950A 8950X 8447A 8447X 8447G	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)
8934 8935 8935X 8936 8936X 8945 8944 8919 8915 8924 8933 8934 8935 8936	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  HIRSES & ATTRICTIONED  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, front Bumper, rear	8954 8950 8955 8950A 8950X 8447A 8447X 8447G 8447R	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
8934 8935 8935X 8936 8936X 8945 8949 8919 8915 8924 8933 8934 8935 8936 8922	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  Hassis & Attachiments  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis	8954 8950 8955 8950A 8950X 8447A 8447A 8447G 8447R 8447 5040	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard)
8934 8935 8935X 8936 8936X 8945 8944 8919 8915 8924 8933 8934 8935 8936 8936 8922 8921	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, front (1), rear (1)  Chassis & Attachments Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis Chassis brace, front	8954 8950 8955 8950A 8950X 8447A 8447X 8447G 8447R	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
8934 8935 8935X 8936 8936X 8945 8944 8919 8915 8924 8933 8934 8935 8936 8922 8921 8987	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  Hassis & Attachiments  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis	8954 8950 8955 8950A 8950X 8447A 8447A 8447G 8447R 8447 5040	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with
8934 8935 8935X 8936 8936X 8945 8944 8919 8915 8924 8933 8934 8935 8936 8936 8922 8921	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, front (1), rear (1)  Chassis & Attachments Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis Chassis brace, front Covers, gear (2)	8954 8950 8955 8950A 8950X 8447A 8447X 8447G 8447R 8447 5040 8953	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex (2)/ 2.5x12 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw
8934 8935 8935X 8936 8936 8945 8944 8919 8915 8924 8933 8934 8935 8936 8922 8921 8987 8923 8925 8938	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis Chassis brace, front Covers, gear (2) Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Shock tower, front (left & right halves)	8954 8950 8955 8950A 8950X 8447A 8447A 8447G 8447R 8447 5040 8953 8956 8956X	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex (2)/ 2.5x12 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4)
8934 8935 8935X 8936X 8936X 8945 8944 8919 8915 8924 8933 8934 8935 8936 8922 8921 8927 8923 8925 8928 8938 8939	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  HISSIS & ATTRICTIONS  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis Chassis brace, front Covers, gear (2) Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Shock tower, front (left & right halves)	8954 8950 8955 8950A 8950X 8447A 8447X 8447G 8447R 8447 5040 8953	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex, (2)/ 2.5x12 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw
8934 8935 8935X 8936X 8945 8945 8949 8919 8915 8924 8933 8934 8935 8936 8922 8921 8987 8923 8925 8938 8939 8945	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  Hassis & Attachiments  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper front Bumper, rear Chassis Chassis brace, front Covers, gear (2) Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Shock tower, front (left & right halves) Shock tower, rear (left & right halves) Skidplate, center	8954 8950 8955 8950A 8950X 8447A 8447X 8447G 8447R 8447 5040 8953 8956 8956X	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4)
8934 8935 8935X 8936X 8945 8944 8919 8915 8924 8933 8934 8935 8936 8936 8922 8921 8987 8923 8925 8938 8939 8945 8944	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  Hassis & Attachiments  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis Chassis brace, front Covers, gear (2) Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Shock tower, front (left & right halves) Shock tower, rear (left & right halves) Skidplate, center Skidplate, front (1), rear (1)	8954 8950 8955 8950A 8950X 8447A 8447A 8447G 8447R 8447 5040 8953 8956 8956X	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex, (2)/ 2.5x12 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw
8934 8935 x 8935 x 8936 x 8945 8944 8919 8915 8924 8933 8934 8936 8936 8922 8921 8987 8923 8925 8928 8929 8945 8944 8976	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  Chassis & Attrohimatis  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis Chassis brace, front Covers, gear (2) Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Shock tower, front (left & right halves) Shock tower, rear (left & right halves) Skidplate, center Skidplate, front (1), rear (1) Wheelie bar	8954 8950 8955 8950A 8950X 8447A 8447X 8447G 8447R 8447 5040 8953 8956 8956X	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4)
8934 8935 8935X 8936X 8936 8945 8944 8919 8915 8924 8933 8934 8935 8936 8922 8921 8987 8923 8925 8938 8939 8945 8944 8976 8976X	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  FIRSIS & ATTRICTION Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis Chassis brace, front Covers, gear (2) Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Shock tower, front (left & right halves) Shock tower, rear (left & right halves) Skidplate, center Skidplate, front (1), rear (1) Wheelie bar, blue	8954 8950 8955 8950A 8950X 8447A 8447A 8447G 8447R 8447 5040 8953 8956 8956X 8956G 8956T 8956R	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex (2)/ 2.5x12 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4)
8934 8935 x 8935 x 8936 x 8945 8944 8919 8915 8924 8933 8934 8936 8936 8922 8921 8987 8923 8925 8928 8929 8945 8944 8976	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis Chassis brace, front Covers, gear (2) Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Shock tower, front (left & right halves) Shock tower, rear (left & right halves) Skidplate, center Skidplate, center Skidplate, front (1), rear (1) Wheelie bar, blue Wheelie bar, green	8954 8950 8955 8950A 8950X 8447A 8447A 8447G 8447R 8447 5040 8953 8956 8956X 8956G	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex, (2)/ 2.5x12 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x5 GS (4)/
8934 8935 8935X 8936X 8936 8945 8944 8919 8915 8924 8933 8934 8935 8936 8922 8921 8987 8923 8925 8938 8939 8945 8945 8946 8976 8976 8976G	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  FIRSIS & ATTRICTION Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis Chassis brace, front Covers, gear (2) Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Shock tower, front (left & right halves) Shock tower, rear (left & right halves) Skidplate, center Skidplate, front (1), rear (1) Wheelie bar, blue	8954 8950 8955 8950A 8950X 8447A 8447X 8447G 8447R 8447 5040 8953 8956 8956X 8956G 8956T 8956R 8956R	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4)/ 3x14mm pin (4)
8934 8935 8935X 8936X 8936 8945 8944 8919 8915 8924 8933 8934 8935 8936 8922 8921 8987 8923 8925 8928 8929 8945 8948 8948 8949 8949 8949 8949 894	Bumper mount, rear Bumper, front Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  HISSIS & ATTRICHINGTIS  Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Covers, gear (2) Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Shock tower, front (left & right halves) Shock tower, rear (left & right halves) Skidplate, center Skidplate, center Skidplate, front (1), rear (1) Wheelie bar, blue Wheelie bar, green Wheelie bar, orange	8954 8950 8955 8950A 8950X 8447A 8447A 8447G 8447R 8447 5040 8953 8956 8956X 8956G 8956T 8956R	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4)/
8934 8935 8935X 8936X 8936X 8945 8944 8919 8915 8924 8933 8934 8935 8936 8922 8921 8921 8923 8925 8928 8928 8929 8945 8944 8976 8976X 8976K 8976R	Bumper mount, rear Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  HISSIS & ATTRICTION Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis Chassis brace, front Covers, gear (2) Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Shock tower, front (left & right halves) Shock tower, rear (left & right halves) Skidplate, center Skidplate, front (1), rear (1) Wheelie bar, green Wheelie bar, green Wheelie bar, orange Wheelie bar, red	8954 8950 8955 8950A 8950X 8447A 8447X 8447G 8447R 8447 5040 8953 8956 8956X 8956G 8956T 8956R 8956R	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4)/ 3x14mm pin (4)
8934 8935 8935X 8936X 8945 8944 8919 8915 8924 8933 8934 8935 8936 8922 8921 8923 8925 8923 8925 8938 8939 8945 8944 8976 8976X 8976K 8976R	Bumper mount, rear Bumper, front (for use with #8990 LED light kit) Bumper, rear Bumper, rear (for use with #8990 LED light kit) Skidplate, center Skidplate, center Skidplate, front (1), rear (1)  HISSIS & ATTRICTION Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9) Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3) Bumper mount, front Bumper mount, rear Bumper, front Bumper, rear Chassis Chassis brace, front Covers, gear (2) Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Shock tower, front (left & right halves) Shock tower, rear (left & right halves) Skidplate, center Skidplate, front (1), rear (1) Wheelie bar, green Wheelie bar, green Wheelie bar, orange Wheelie bar, red	8954 8950 8955 8950A 8950X 8447A 8447A 8447G 8447R 8447 5040 8953 8956 8956X 8956G 8956T 8956R 8654 8654G	driveshaft) Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft, center, aluminum Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Oil, differential (20M weight) (standard) Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4)/ 3x14mm pin (4)

Page 2	Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio 8	& TSM (N	Nodel 89076-4) Parts List
8654R	Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4)/	2535	Screws, 4x10mm countersunk machine (hex drive) (6)
	3x14mm pin (4)	3937	Screws, 4x12mm button-head machine (hex drive) (6)
8957	Wheel washers, black (4)	3938	Screws, 4x14mm button-head machine (hex drive) (6)
8957X	Wheel washers, blue (4)	3933	Screws, 4x16mm button-head machine (hex drive) (6)
8957G	Wheel washers, green (4)	2589	Screws, 4x20mm button-head machine (hex drive) (6)
8957T	Wheel washers, orange (4)	2596	Screws, 4x25mm button-head machine (hex drive) (6)
8957R	Wheel washers, red (4)	2595	Screws, 4x35mm button-head machine (hex drive) (6)
	Front Suspension & Steering	8940X	Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS
8926	Bulkhead tie bar, front, upper (1)/ lower (2) (steel)		(14)/ 3x6mm BCS (4)/ retainers (8)
8920	Bulkhead, front (upper and lower)		LED Lights
8932X	Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4)	6590	High-Voltage Power Amplifier
8932G	Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left	8990	LED light kit, Maxx®, complete (includes #6590 high-voltage
	& right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4)		power amplifier)
8932A	Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized),		Motors & Electronics
	left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4)	7749	Adapter, standard servo (adapts standard servo to fit in X-Maxx®
8932R	Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left &	1143	or Maxx®)
0022	right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4)	3463	Cooling fan kit (with shroud), Velineon® 540XL motor
8932 8916	Caster blocks (c-hubs), left & right  Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear	3475	Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)
0910	(2)	8987	Covers, gear (2)
8947	Servo horn, steering/ linkage, steering (46mm, assembled with pivot	2092	Gear set (for 2090 servo)
	balls)	3462	Heat sink, Velineon® 540XL motor
8938	Shock tower, front (left & right halves)	8960	Motor mounts (front and rear)/ pin (1)
8946	Steering bellcranks/ bellcrank support/ servo saver/ servo saver	3461	Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with
	spring/ draglink/ 3x20mm shoulder screws (2)	0.404	12-gauge wire and gold-plated bullet connectors) (for Maxx®)
8937X	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right	3464	Mount, motor cooling fan (fits #3461 motor)
8937G	Steering blocks, 6061-T6 aluminum (green-anodized), left & right	2091 2090	Servo case/ gaskets (for 2090 waterproof servo) Servo, digital high-torque (ball bearing), waterproof
8937A	Steering blocks, 6061-T6 aluminum (orange-anodized), left & right	3465	Velineon® VXL-4s Electronic Speed Control, waterproof (brushless)
8937R	Steering blocks, 6061-T6 aluminum (red-anodized), left & right	3403	(fwd/rev/brake)
8937	Steering blocks, left & right		Radio System, Batteries & Chargers
8930	Suspension arm, lower, black (left or right, front or rear) (2)	00 40 V	
8930X	Suspension arm, lower, blue (left and right, front or rear) (2)	2849X 2872X	4000mAh 11.1v 3-Cell 25C LiPo Battery
8930G	Suspension arm, lower, green (left and right, front or rear) (2)	2888X	5000mAh 11.1v 3-Cell 25C LiPo Battery 5000mAh 14.8v 4-Cell 25C LiPo Battery
8930T	Suspension arm, lower, orange (left and right, front or rear) (2)	2889X	5000mAh 14.8v 4-Cell 25C LiPo Battery
8930R	Suspension arm, lower, red (left and right, front or rear) (2)	2857X	6400mAh 11.1v 3-Cell 25C LiPo Battery
8930A	Suspension arm, lower, white (left and right, front or rear) (2)	2878X	8400mAh 11.1v 3-Cell 25C LiPo Battery
8929	Suspension arms, upper, black (left or right, front or rear) (2)	2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries
8929X 8929G	Suspension arms, upper, blue (left or right, front or rear) (2)		to separate balance ports)
8929G 8929T	Suspension arms, upper, green (left or right, front or rear) (2) Suspension arms, upper, orange (left or right, front or rear) (2)	1926	Antenna caps, vinyl (2)/ antenna spool
8929R	Suspension arms, upper, red (left or right, front or rear) (2)	1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
8929A	Suspension arms, upper, white (left or right, front or rear) (2)	1726A	Antenna, tube, black (1)/ vinyl antenna cap (1)/ wire retainer (1)
8940X	Suspension pin set, complete (hardened steel), 4x64mm (4),	2943	Battery charge indicators (green (4), blue (4), grey (4))
	4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS	6548	Battery door, transmitter (replacement for #6516, 6517, 6528, 6529, 6530 transmitters)
	(14)/ 3x6mm BCS (4)/ retainers (8)	2914	Battery, Power Cell AA Alkaline (4)
8941	Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened	2996	Battery/charger completer pack (includes #2971 iD charger (1),
9040	steel)		#2888X 5000mAh 14.8V 4-cell 25C LiPo battery (1))
8940	Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)	2990	Battery/charger completer pack (includes #2972 Dual iD®
			charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo battery (2))
	Hardware	2972	Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery
3642	Attachment screws, shock (3x12mm shoulder screws) (6)	2973	Identification Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto
1552	Backplate screws (3x8mm cap-head machine) (6)/washers (6)/	29/3	Battery Identification
2584	wrench Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX 2.5,	2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery
2304	2.5R, 3.3)		Identification
8447A	Nuts, 5mm flanged nylon locking (aluminum, black-anodized,	2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto
	serrated) (4)		Battery Identification
8447X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized,	6525	Communication link, telemetry expander
	serrated) (4)	2092	Gear set (for 2090 servo)
8447G	Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)	2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)
8447R	Nuts, 5mm flanged nylon locking (aluminum, red-anodized,	2968	LiPo cell voltage checker/balancer (requires #2938X adapter for
	serrated) (4)		Traxxas® iD® batteries)
8447	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)	6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)
5147X	Nuts, 5mm flanged nylon locking (steel, serrated) (8)	6552	Seal kit, expander box (includes o-ring, seals, and silicone
3236	Screws, 2.5x12mm cap-head machine (6)	0500	grease)
2577	Screws, 3x10mm button-head machine (hex drive) (6)	6526	Sensor, auto-detectable, temperature
2587	Screws, 3x10mm cap-head machine (6) (no washer)	6527 6521	Sensor, auto-detectable, voltage Sensor, temperature and voltage (long)
2551	Screws, 3x10mm countersunk machine (6) (hex drive)	2091	Servo case/ gaskets (for 2090 waterproof servo)
4859 2578	Screws, 3x10mm flat-head machine (hex drive) (4)	2091	Servo, digital high-torque (ball bearing), waterproof
2578 2579	Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6)	6553X	Telemetry expander 2.0 and GPS module 2.0, TQi radio system
2579 2553	Screws, 3x15mm button-nead machine (nex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive)	6550X	Telemetry expander 2.0, TQi radio system (compatible only with
3646	Screws, 3x15mm flat-head machine (hex drive) (6)		#6551X GPS module)
2583	Screws, 3x18mm button-head machine (hex drive) (6)	6551X	Telemetry GPS module 2.0, TQi radio system (compatible only
2581	Screws, 3x25mm button-head machine (hex drive) (6)		with #6550X telemetry expander)
2582	Screws, 3x30mm button-head machine (hex drive) (6)	6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™
2550	Screws, 3x8mm countersunk machine (6) (hex drive)		enabled, TSM (2-ch transmitter, 5-ch micro receiver)
3936	Screws, 4x10mm button-head machine (hex drive) (6)		

6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas	6490X	Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
307K	Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver)	6491X	(compatible with steel spur gears)  Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
528	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-channel (transmitter only)	6494X	(compatible with steel spur gears) Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
529	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only)	6495X	(compatible with steel spur gears) Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
530	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output,		(compatible with steel spur gears)
511	4-channel (transmitter only) Traxxas Link™ Wireless Module	6496X	Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
	Ready-To-Race Model	6447 6447X	Spur gear, 46-tooth (1.0 metric pitch) Spur gear, 46-tooth, steel (1.0 metric pitch)
9076-4	Maxx®: 1/10 Scale 4WD Brushless Electric Monster Truck with TQi	6447R	Spur gear, 46-tooth, steel (vide-face, 1.0 metric pitch)
	Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)®	6448	Spur gear, 50-tooth (1.0 metric pitch)
	Rear Suspension	6448X 6448R	Spur gear, 50-tooth, steel (1.0 metric pitch) Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
927	Bulkhead tie bar, rear, upper (1)/ lower front (1)/ lower rear (1) (steel)	6449	Spur gear, 54-tooth (1.0 metric pitch)
928	Bulkhead, rear (upper and lower)	6449X	Spur gear, 54-tooth, steel (1.0 metric pitch)
952X	Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (2)		Steering Components
952G	Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear) (2)	2728	Ball bearings (5x8x2.5mm) (2)
952 <b>952A</b>	Carriers, stub axle (left & right)  Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rear)	7020	Ball bearings, blue rubber sealed (8x12x3.5mm) (2)
002/1	(2)	8947	Servo horn, steering/ linkage, steering (46mm, assembled with pivo
952R	Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2)	8946	balls) Steering bellcranks/ bellcrank support/ servo saver/ servo saver
916	Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear	0010	spring/ draglink/ 3x20mm shoulder screws (2)
939	(2) Shock tower, rear (left & right halves)	8948X	Toe links, front (TUBES blue-anodized, 7075-T6 aluminum,
930	Suspension arm, lower, black (left or right, front or rear) (2)		stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends front (4)/ aluminum wrench (1)
930X	Suspension arm, lower, blue (left and right, front or rear) (2)	8948G	Toe links, front (TUBES green-anodized, 7075-T6 aluminum,
930G	Suspension arm, lower, green (left and right, front or rear) (2)		stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends
930T 930R	Suspension arm, lower, orange (left and right, front or rear) (2) Suspension arm, lower, red (left and right, front or rear) (2)		front (4)/ aluminum wrench (1)
930A	Suspension arm, lower, red (left and right, front or rear) (2)	8948A	Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends
929	Suspension arms, upper, black (left or right, front or rear) (2)		front (4)/ aluminum wrench (1)
929X	Suspension arms, upper, blue (left or right, front or rear) (2)	8948R	Toe links, front (TUBES red-anodized, 7075-T6 aluminum,
929G	Suspension arms, upper, green (left or right, front or rear) (2)		stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends
929T 929R	Suspension arms, upper, orange (left or right, front or rear) (2)	8948	front (4)/ aluminum wrench (1)  Toe links, molded composite, 100mm (89mm center to center) (bla
929K 929A	Suspension arms, upper, red (left or right, front or rear) (2) Suspension arms, upper, white (left or right, front or rear) (2)	0340	(2)
940X	Suspension pin set, complete (hardened steel), 4x64mm (4),		Suspension Linkage
	4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS	8941	Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened
044	(14)/ 3x6mm BCS (4)/ retainers (8)	0011	steel)
941	Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)	8940	Suspension screw pin set, front or rear (hardened steel), 4x18mm (
940	Suspension screw pin set, front or rear (hardened steel), 4x18mm (4),	8948X	4x38mm (2), 4x33mm (2), 4x43mm (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum,
	4x38mm (2), 4x33mm (2), 4x43mm (2)	03407	stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends
	Shocks (GT-Maxx®)		front (4)/ aluminum wrench (1)
965X	Body, GT-Maxx® shock (aluminum, blue-anodized) (1)	8948G	Toe links, front (TUBES green-anodized, 7075-T6 aluminum,
965G	Body, GT-Maxx® shock (aluminum, green-anodized) (1)		stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends front (4)/ aluminum wrench (1)
965T 965R	Body, GT-Maxx® shock (aluminum, orange-anodized) (1) Body, GT-Maxx® shock (aluminum, red-anodized) (1)	8948A	Toe links, front (TUBES orange-anodized, 7075-T6 aluminum,
962	Rebuild kit, GT-Maxx® shocks (lower cartridge, assembled, pistons,		stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends
	piston nuts, bladders) (renews 2 shocks)	8948R	front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum,
964X	Shock caps, aluminum (blue-anodized), GT-Maxx® shocks (4)	0940K	stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends
964G	Shock caps, aluminum (green-anodized), GT-Maxx® shocks (4)		front (4)/ aluminum wrench (1)
964T 964R	Shock caps, aluminum (orange-anodized), GT-Maxx® shocks (4) Shock caps, aluminum (red-anodized), GT-Maxx® shocks (4)	8948	Toe links, molded composite, 100mm (89mm center to center) (black)
964	Shock caps, GT-Maxx® shocks/ spring perch/ adjusters/ 2.5x14 CS		(2)
	(2) (for 2 shocks)		Team Traxxas Items
963	Shock shaft, 72mm (GT-Maxx®) (steel, chrome finish) (2)	2514	Decal sheet, racing sponsors
961	Shocks, GT-Maxx®, aluminum (blue-anodized) (fully assembled w/o springs) (2)	9950 9909	Official Team Traxxas® racing decal set (flag logo/ 6-color) Traxxas® racing banner, red & black (3x7 feet)
961R	Shocks, GT-Maxx®, aluminum (red-anodized) (fully assembled w/o	99U8	Tires & Wheels
667	springs) (2) Silicono shock oil (30 wt) 60cc	8447A	Nuts, 5mm flanged nylon locking (aluminum, black-anodized,
968X	Silicone shock oil (30 wt), 60cc  Spring retainer (adjuster), blue-anodized aluminum, GT-Maxx®	V AIR	serrated) (4)
	shocks (4) (assembled with o-ring)	8447X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized,
968G	Spring retainer (adjuster), green-anodized aluminum, GT-Maxx®	8447G	serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized,
968A	shocks (4) (assembled with o-ring) Spring retainer (adjuster), orange-anodized aluminum, GT-	0-7 <b>-7</b> 1 <b>G</b>	serrated) (4)
	Maxx® shocks (4) (assembled with o-ring)	8447R	Nuts, 5mm flanged nylon locking (aluminum, red-anodized,
968R	Spring retainer (adjuster), red-anodized aluminum, GT-Maxx®	0447	serrated) (4)
000	shocks (4) (assembled with o-ring)	8447 <b>5147X</b>	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)  Nuts, 5mm flanged nylon locking (steel, serrated) (8)
966 967	Springs, shock (natural finish) (GT-Maxx®) (1.210 rate) (2)	<b>5147X</b> 8972	Tires & wheels, assembled, glued (black wheels, Maxx® All-Terrain
967 <b>969</b>	Springs, shock (natural finish) (GT-Maxx®) (1.450 rate) (2) Springs, shock (natural finish) (GT-Maxx®) (1.725 rate) (2)	55. <u>L</u>	tires, foam inserts) (2) (17mm splined) (TSM® rated)
	Spur Gears & Pinion Gears	8972A	Tires & wheels, assembled, glued (black, blue beadlock style
197V	_		wheels, Maxx® MT tires, foam inserts) (2) (17mm splined) (TSM
6487X	Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)	8972T	rated) Tires & wheels, assembled, glued (black, orange beadlock styl
			wheels, Maxx® MT tires, foam inserts) (2) (17mm splined) (TSM
489X	Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw		

#### Page 4 Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 89076-4) Parts List

8948A

8948R

rage <del>-</del>	maxxe. Tel Traxxas Ellik Ellabica 2OTIZ Radio
8972R	Tires & wheels, assembled, glued (black, red beadlock style wheels, Maxx® MT tires, foam inserts) (2) (17mm splined) (TSM® rated)
8972X	Tires & wheels, assembled, glued (black, satin chrome beadlock style wheels, Maxx® MT tires, foam inserts) (2) (17mm splined) (TSM® rated)
8970	Tires, Maxx® All-Terrain 2.8" (2)/ foam inserts (2)
8956	Wheel hubs, hex (2)/ 2.5x12 pins (2)
8956X	Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4)
8956G	Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4)
8956T	Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4)
8956R	Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4)
8654	Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4)/ 3x14mm pin (4)
8654G	Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4)/ 3x14mm pin (4)
8654A	Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4)/ 3x14mm pin (4)
8654R	Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4)/ 3x14mm pin (4)
8957	Wheel washers, black (4)
8957X	Wheel washers, blue (4)
8957G	Wheel washers, green (4)
8957T	Wheel washers, orange (4)
8957R	Wheel washers, red (4)
8971	Wheels (black) (2)
	Transmission Components
	- (-)

	i i dilaliliaalon oompononta
8987	Covers, gear (2)
8985	Input gear, transmission, 22-tooth/ 2.5x12mm pin
8986	Input shaft, transmission
5040	Oil differential (20M weight) (standard)

### Traxxas Tools

3433X	Body reamer (aluminum handle)
3433	Body reamer (plastic handle)
3436	Cap, body reamer
3432	Scissors, curved tip
3431	Scissors, straight tip
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive
8721	Speed bit handle, medium (one piece)
8720	Speed bit handle, premium, large (rubber overmold)
8722	Speed bit handle, premium, medium (rubber overmold)
8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm, 7.00mm, 8.00mm),
8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive
8719	Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm), 1/4" drive
8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive
3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle
	Turnhuckles a Threaded Dade

#### Turnbuckles & Threaded Rods

8948X	Toe links, front (TUBES blue-anodized, 7075-T6 aluminum,
	stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends,
	front (4)/ aluminum wrench (1)

8948G Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)

Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)

Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends,

front (4)/ aluminum wrench (1)

8948 Toe links, molded composite, 100mm (89mm center to center) (black) (2)

If you have questions or need technical assistance, call Traxxas at:

## 1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM